

The Tiffany T80S (single shown here) and the T80T (twin) are full security, tamper-resistant, full-height turnstiles. Both are equipped with Ovaline arms.



8641 S. Warhawk Rd. Conifer, CO 80433
Patrick.McAllister@TURNSTILES.us
(303) 670-1099 (303) 679-8949 fax



In-Service World-Wide

T80 Series (Single or Twin)

The T80S (single, shown above) and T80T (twin) are full security, tamper-resistant, full-height turnstiles. Both are equipped with Ovaline arms measuring 1/2" x 2" x 24".

T80S (Single)

Exterior Height: 89.5"
Width: 65.68"
Pedestrian Clearance: 30"

T80T (Tandem)

Exterior Height: 89.5"
Width: 96.18"
Pedestrian Clearance: 30"



Available as a Metal-Detect Door where higher security needs exist. Metal detection and bullet-resistant panels are available in varying performance specs based on your application.

Applications:

The Tiffany T80 is a three-vane turnstile with a weather resistant finish and is ideal for interior or exterior placement – wherever style and durability are needed. It is crafted of 6005-T6 aluminum extrusions and features GE's transparent Lexan polycarbonate cage panels.

Product Features:

Materials and Finishes available in your choice of:

- Available in your choice of Clear, Dark Bronze or Black
- Performance features include automatic indent Feather-Touch action – that includes shock suppressor technology and a non-entrapment design

Design & Construction:

- Designed for secure operation with aesthetics in mind
- Features minimal exposed hardware and meets ASTM standards

Controller &

Access Control Operation:

- Self-centering control head with adjustable hydraulic shock suppression
- Hardened tool steel locking bars, cam and roller assemblies
- Permanently lubricated bearings
- All units are available in clockwise, counter-clockwise or bi-directional passage

Measures:

T80S (Single)

Exterior Height
89.5"
Width
65.68"
Pedestrian Clearance
30"

T80T (Tandem)

Exterior Height
89.5"
Width
96.18"
Pedestrian Clearance
30"

Options:

- Electronic locking module featuring heavy-duty 24 vdc pull-type industrial solenoids and card reader interface
- Available in Fail-Safe (open on power failure) or Fail-Lock (lock on power failure modes)
- Can interface with card readers, computer attendance systems, coin and token acceptors, push buttons, wireless remote controls and metal detectors
- Electronic 6 digit resettable counter with LCD display and ten-year lithium battery
- Vertical Graphic Array (VGA) red x / green arrow
- Additional options available on request

Matching Swing Gate available

(see model SGH36 Manual Passage Gate information)



Electrical Specifications:

Command module input 110-240 VAC (2 amp-1 amp) 50-60 Hz; control voltage 24 VDC.



All electrical components are UL recognized and CSA certified.

Warranty:

Units are warranted against defects in materials and workmanship for a period of one year from date of delivery. See warranty information for specific details.



T80S



T80T

